

### Tique Wall Systems Exterior Textured Finishes Fine Sand, Medium Sand, Medium Swirl, Coarse Swirl, Freestyle

#### TECHNICAL DATA

REPORT	TEST METHOD	TEST CRITERIA	TEST RESULTS
Surface Burning	ASTM E-84	< 25 Flame Spread < 450 Smoke Developed	Pass Pass
Flexibility	ASTM D-522	4" mandrel bend	Pass
Water Vapor Transmission	ASTM E-96	28 days	Pass
Accelerated Weathering	ASTM G-154	2000 hours	Pass; No deleterious effects
Freeze-thaw Resistance	ASTM 2485	60 cycles	No deleterious effects; 90 cycles
Mildew Resistance	ASTM D-3273	No growth @ 28 days	Pass
Salt Spray Resistance	ASTM B-117	300 hours	Pass; No deleterious effects
Water Resistance	ASTM D-2247	14 days	Pass; No deleterious effects
Abrasion Resistance	ASTM D-968	528 qts. sand	No cracking, checking or Loss of film integrity @ 528 qts.
Adhesion	ASTM C-297	28 days	> 90 to concrete
Fire Resistance	ASTM E-119	No effect on fire resistance rating of Existing rated assembly	Pass; Classified UL

*Tique Wall Systems Exterior Textured Finishes are a ready-mixed, 100% acrylic based exterior textured coating used as a decorative wall finish over all approved basecoats, prepared concrete, masonry and plaster substrates.*

#### Coverage

Tique Wall Systems Freestyle  
Varies with technique.

Tique Wall Systems Fine Sand Finish:  
117-130 ft<sup>2</sup> (10.9-12.1 m<sup>2</sup>) per pail.

Tique Wall Systems Medium Sand  
Finish: 105- 117 ft<sup>2</sup> (9.75-10.9 m<sup>2</sup>) per  
pail.

Tique Wall Systems Coarse Sand Fin-  
ish: 77– 90 ft<sup>2</sup> (7.2-8.4 m<sup>2</sup>) per pail.

Tique Wall Systems Fine Swirl Finish:  
113-126 ft<sup>2</sup>  
(10.5-11.7 m<sup>2</sup>) per pail.

Tique Wall Systems Medium Swirl  
Finish: 117 -130 ft<sup>2</sup> (10.9-12.1m<sup>2</sup>) per  
pail.

\*Coverages may vary depending on  
application technique and surface  
conditions

#### FEATURES BENEFITS

<b>Integral Color</b>	Reduced recoating and maintenance; Unlimited Color Options
<b>Weather Resistant</b>	Repulsion of water and resistance of wind-driven rain
<b>Breathable</b>	Resists blistering, peeling and flaking; breathes naturally

#### Packaging

5 gal pail 68.5 lbs / 31kg per pail

#### Shelf Life

24 months, if properly sealed and  
stored.

#### Storage

Store off the ground in a cool/dry  
area. Protect from extreme heat  
[90°F (32°C)], moisture and direct  
sunlight.

## Tique Wall Systems Exterior Textured Finishes Fine Sand, Medium Sand, Medium Swirl, Coarse Swirl, Freestyle

### SURFACE PREPARATION

**Concrete and masonry surfaces:** Surfaces must be clean, dry, and free of frost, damage, releasing agents, including dirt, efflorescence, form oil and other foreign matter. Loose or damaged material must be removed by water blasting, sandblasting or mechanical wire brushing and repaired. Avoid application over irregular surfaces. Resurface, patch or level surfaces to required tolerance and smoothness with appropriate Tique Wall Systems leveling materials.

#### Exterior Insulation and Finish

**Tique Wall Systems Systems (EIFS):** Surface must be free of all releasing agents.

**Gypsum wallboard surfaces:** Wallboard must be taped and fasteners spotted with joint compound. Surface must be free of dust, dirt and releasing agents. Prime with appropriate Tique Wall Systems Primer.

**Tique Wall Systems recommends priming cementitious substrates using Tique Wall Systems primer prior to application of finish.**

### MIXING

Mix with a clean, rust-free electric drill and paddle to a uniform consistency. A small amount of clean water may be added to aid workability. Limit addition of water to amount needed to achieve the finish texture. Additives are not permitted. Close container when not in use. Clean tools with water immediately after use.

### APPLICATION

Apply only to sound and clean, dry, properly prepared surfaces.

**Trowel:** Apply Tique Wall Systems Textured Finish with a clean stainless steel trowel to a rough thickness slightly more than the largest aggregate size. Apply the finish keeping thickness uniform. Maintain a wet edge on Tique Wall Systems Textured Finish by applying and texturing continually over the wall surface. Work Tique Wall Systems Textured Finish to corners, joints or other natural breaks. Do not allow material to set up within an uninterrupted wall area. Achieve final texture by floating with the appropriate trowel.

Note: Tique Wall Systems Freestyle Finish requires two coats.

### Tique Wall Systems Exterior Textured Finishes Fine Sand, Medium Sand, Medium Swirl, Coarse Swirl, Freestyle

#### APPLICATION Continued

**Spray:** Tique Wall Systems Textured Finishes can be applied with a gravity-feed sprayer, texture spray pump machine, or other appropriate equipment. To ensure full coverage of the surface, apply in an even coat.

IMPORTANT: ALWAYS check color for proper match.

Apply coating continuously, maintain a wet edge to eliminate cold joints. Work Tique Wall Systems Textured Finish to corners, joints or other natural breaks. Avoid application in direct sunlight. Protect installed product from rain, freezing, and continuous high humidity until completely dry.

#### Curing/Drying

Tique Wall Systems Textured Finishes dry within 24 –72 hours under normal conditions [70°F (21°C), 50% RH]. Drying time varies with temperature, humidity and surface conditions.

#### Clean Up

Clean tools and equipment with water immediately after use. Remove dried material from tools and equipment mechanically.

#### LIMITATIONS

Use Tique Wall Systems Textured Finishes only when surface and ambient temperatures are above 40°F (4°C) and below 100°F (38°C) during application and drying period.

Store Tique Wall Systems materials in a cool, dry place.

Sloped surfaces: Refer to Tique Wall Systems details.

Tique Wall Systems Textured Finishes should not be used on weather-exposed horizontal or below grade surfaces or where immersion in water may occur.

Do not apply Tique Wall Systems Textured Finish to frozen surfaces.

#### HEALTH AND SAFETY

##### Health Precaution

Tique Wall Systems Textured Finishes are water-based. As with any chemical construction product, exercise care when handling.

##### WARNING!

Causes eye and skin irritation.

##### Safety Precaution

Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

##### First Aid:

**EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eye lids with fingers. Get immediate medical attention.

**SKIN CONTACT:** Immediately wash skin with plenty of soap and water for at least 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

**INHALATION:** If inhaled, remove to fresh air. If not breathing give artificial respiration or give oxygen by trained personnel. Seek medical attention immediately.

**INGESTION:** If swallowed, do NOT induce vomiting. Call a physician or a poison control center immediately. Never give anything by mouth to an unconscious person.

##### Spills

Contain and clean with appropriate absorbent materials.

##### Disposal

Dispose of in accordance with local, state or federal regulations.

##### Warning

KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY. Consult the Safety Data Sheet (SDS) for further health and safety information.

##### LIMITED WARRANTY

This product is subject to a written limited warranty. Refer to Tique Wall Systems Specifications for more complete information on proper use and handling of this product.



697 Oakwood Ave  
West Hartford, CT 06110  
860-761-2831

This product is intended for use by qualified professional contractors. All information conforms to the standard detail recommendations and specifications for the installation of Tique Wall Systems and is presented in good faith as of the date of publication of this document. GREENMAKER INDUSTRIES ASSUMES NO LIABILITY, EXPRESSED OR IMPLIED, AS TO THE WORKMANSHIP, ENGINEERING OR ARCHITECTURE OF ANY PROJECT. For more information regarding this product or additional Tique Wall Systems products, please contact a Tique Wall Systems Representative at (860) 761-2830 or visit our website [www.TiqueWallSystems.com](http://www.TiqueWallSystems.com).