

### Tique Primer

64 Standard Colors / Custom Colors

#### TECHNICAL DATA

REPORT	TEST METHOD	TEST CRITERIA	TEST RESULTS
Surface Burning	ASTM E-84	< 25 Flame Spread	Pass
		< 450 Smoke Developed	Pass

#### FEATURES BENEFITS

<b>Acrylic Based</b>	Excellent adhesion; finish coat adhesion improvement
<b>Tinted for Finish</b>	Color uniformity improvement
<b>Substrate Absorption</b>	Improves coverage, water-resistance, and reduces possible efflorescence
<b>Non Vapor Barrier</b>	Allows substrate to breathe naturally
<b>Water-Based</b>	Safe, non-toxic; cleans up with water
<b>Low VOC</b>	Safe for workers and the environment

#### SURFACE PREPARATION

Surfaces must be clean, dry, and free of frost, damage, releasing agents, including dirt, efflorescence, form oil and other foreign matter. Loose or damaged material must be removed by water blasting, sandblasting or mechanical wire brushing and repaired. Avoid application over irregular surfaces. Resurface, patch or level surfaces to required tolerance and smoothness with appropriate Tique leveling materials.

Pressure washing is a recommended means of surface preparation. Follow necessary safety precautions and adjust pressure to avoid damage to the underlying substrate or substrate condition. For mold, algae, and mildew removal, treat surfaces with a commercial mildew removal and/or wash product carefully following manufacturer's application and safety directions.

*Tique Primer is used for priming prepared concrete, masonry, plaster, EIFS base coat, or drywall surfaces prior to application of Tique Finishes and Coatings.*

#### Coverage

800-1000 ft<sup>2</sup> (74.3-92.9 m<sup>2</sup>) per pail applied at 4 to 6 wet mils per coat

#### Packaging

5 gal pail (19L) 47.5 lbs / 21.6 kg per pail

#### Shelf Life

24 months, if properly sealed and stored.

#### Storage

Store off the ground in a cool/dry area. Protect from extreme heat [90°F (32°C)], moisture and direct sunlight.

### Tique Primer

64 Standard Colors / Custom Colors

#### MIXING

Mix with a clean, rust-free electric drill and paddle to a uniform consistency. Close container when not in use. Clean tools with water immediately after use.

#### APPLICATION

Apply only to sound and clean, dry, properly prepared surfaces.

##### **Airless Spraying:**

Use airless sprayer with minimum 19 mil tip. Use a starting pressure of 1900 psi and adjust as necessary.

##### **As a primer:**

Apply at 4-6 wet mils per coat. Multiple coats may be required, depending on surface condition.

##### **Curing/Drying Time**

Times assume 70° F (21° C) and 50% relative humidity. Drying time varies with temperature/humidity and surface conditions. Protect installed product from rain, freezing, and continuous high humidity until completely dry.

##### **Clean Up**

Clean all tools and equipment immediately with water. Cured material may be removed by mechanical means.

#### LIMITATIONS

- Use Tique Primer only when surface and ambient temperatures are above 40°F (4°C) and below 100°F (38°C) during application and drying period.
- Store Tique materials in a cool, dry place.
- Sloped surfaces: Refer to Tique details.
- Tique Primer should not be used on horizontal surfaces unless protected with appropriate Tique Finish materials.
- Do not apply Tique Primer to frozen surfaces.

#### HEALTH AND SAFETY

##### **Health Precaution**

Tique Primer is water-based. As with any chemical construction product, exercise care when handling.

##### **WARNING!**

Causes eye and skin irritation.

##### **Safety Precaution**

Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

##### **First Aid:**

**EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eye lids with fingers. Get immediate medical attention.

**SKIN CONTACT:** Immediately wash skin with plenty of soap and water for at least 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

**INHALATION:** If inhaled, remove to fresh air. If not breathing give artificial respiration or give oxygen by trained personnel. Seek medical attention immediately.

**INGESTION:** If swallowed, do NOT induce vomiting. Call a physician or a poison control center immediately. Never give anything by mouth to an unconscious person.

##### **Spills**

Contain and clean with appropriate absorbent materials.

##### **Disposal**

Dispose of in accordance with local, state or federal regulations.

##### **Warning**

KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY. Consult the Safety Data Sheet (SDS) for further health and safety information.

##### **LIMITED WARRANTY**

This product is subject to a written limited warranty. Refer to Tique Specifications for more complete information on proper use and handling of this product.



697 Oakwood Avenue, West Hartford, CT 06110  
voice: 860.761.2830 fax: 860.761.2831  
www.decoplast.com

This product is intended for use by qualified professional contractors. All information conforms to the standard detail recommendations and specifications for the installation of Tique systems and is presented in good faith as of the date of publication of this document. GREENMAKER INDUSTRIES ASSUMES NO LIABILITY, EXPRESSED OR IMPLIED, AS TO THE WORKMANSHIP, ENGINEERING OR ARCHITECTURE OF ANY PROJECT. For more information regarding this product or additional Tique products, please contact a Tique Representative at (860) 761-2830 or visit our website [www.Tiquewall.com](http://www.Tiquewall.com).